



PVL **YUKO SUPER GAS 10W-40**

Teilsynthetisches Motorenöl für erdgasbetriebene Motoren

Beschreibung

Premium quality semy-synthetic motor oil intended for modern gasoline and diesel engines operating on natural gas (LPG - a mixture of propane and butane or CNG - methane) of passenger cars, vans and light trucks.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 10W-40.

Compatible with injector engines, including turbocharged with intercooler and catalyst.


Containertypen

 Canister 4L

 Canister 5L

 Tin bucket 20L

 Barrel 200L

 In bulk

Vorteile

- Hohe Leistung unter verschiedenen Betriebsbedingungen - in der Stadt und im Start-Stopp"-Modus;
- Gute Schaum- und Korrosionsbeständigkeit, kompatibel mit Dichtungsmaterialien;
- Erhöhte Motorsauberkeit durch den hohen Anteil an synthetischen Komponenten;
- Stabiles Viskositätsverhalten während der gesamten Betriebszeit durch die außergewöhnliche Stabilität aller Komponenten;

Erfüllt Spezifikationen

SAE 10W-40 | API SJ/CF |

Typische Kennwerte

Kinematic viscosity at 100°C, mm ² /s	14,9
Density at 20°C, kg/m ³	886
Viscosity index	136
Alkalinity, mg KOH/g	5.8
Flash point in open crucible, °C	218
Pour point, °C	-30

Temperaturbereich



Produced according to TU U 19.2-31852954-073:2015. This information is reference and it can be changed without a notice. This article is from 01/03/2016, it replaces all the early published descriptions of the product.