YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



PVL

YUKO SUPER GAS 10W-40

Teilsynthetisches Motorenöl für erdgasbetriebene Motoren

Beschreibung

Premium quality semy-synthetic motor oil intended for modern gasoline and diesel engines operating on natural gas (LPG - a mixture of propane and butane or CNG - methane) of passenger cars, vans and light trucks.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 10W-40.

Compatible with injector engines, including turbocharged with intercooler and catalyst.

Containertypen

Canister 4L | Canister 5L | Tin bucket 20L | Barrel 200L | In bulk

Vorteile

- Hohe Leistung unter verschiedenen Betriebsbedingungen - in der Stadt und im Start-Stopp"-Modus;
- Gute Schaum- und Korrosionsbeständigkeit, kompatibel mit Dichtungsmaterialien;
- Erhöhte Motorsauberkeit durch den hohen Anteil an synthetischen Komponenten;
- Stabiles Viskositätsverhalten während der gesamten Betriebszeit durch die außergewöhnliche Stabilität aller Komponenten;

Erfüllt Spezifikationen

SAE 10W-40 | API SJ/CF |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14,9
Density at 20˚C, kg/m³	886
Viscosity index	136
Alkalinity, mg KOH/g	5.8
Flash point in open crucible, ˚C	218
Pour point, ˚C	-30

Temperaturbereich

-27˚C 0 ˚C +45˚C

Produced according to TU U 19.2-31852954-073:2015. This information is reference and it can be changed without a notice. This article is from 01/03/2016, it replaces all the early published descriptions of the product.