# Produktdatenblat
# Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com




CVL

# YUKO TAD-17i (GL-5, SAE 85W-90)

## Universelles klassisches Ganzjahres-Getriebeöl.

## Beschreibung

Bestimmt für die Schmierung aller Getriebearten, einschließlich hochbelasteter, hypoidaler Getriebe, von Lastkraftwagen u nd Pkw, Traktoren u nd anderen mobilen Fahrzeugen.
Hergestellt aus hochwertigen Grundölen mit effektiven Additiven.

## Containertypen

OILBOX 20L | Tin bucket 20L | Canister 20L | Barrel 200L | In bulk

## Vorteile

- Bietet einen hohen Verschleißschutz in einem weiten Lastbereich
- Geringe Flüchtigkeit bei hohen Betriebstemperaturen;
- Gleichbleibend hohe Leistung in verschiedenen Betriebsarten;
- Hat gute Schaum- und Korrosionsschutzeigenschaften, kompatibel mit Dichtungsmaterialien.

## Erfüllt Spezifikationen

**SAE 85W-90 | API GL-5 |**

## Typische Kennwerte

| | |
|---|---|
| Kinematic viscosity at 100˚C, mm²/s | 19,1 |
| Density at 20˚C, kg/m³ | 893 |
| Viscosity index | 102 |
| Acid index, mg KOH/g | 0.5 |
| Flash point in open crucible, ˚C | 230 |
| Pour point, ˚C | -25 |

**Temperaturbereich**

-18˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-002-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.