Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL SP

YUKO TM-4 80W-85

Ganzjahres-Getriebeöl API GL-4.

Beschreibung

YUKO TM-4 80W-85 für Frontantriebsgetriebe u nd Getriebe aller Art, die ein Öl der API GL-4-Klassifizierung erfordern.

Containertypen

Tin bucket 20L

Barrel 200L

In bulk

Vorteile

- Hat einen ausgezeichneten Verschleißschutz, extremen Druck, Antioxidations- und Korrosionsschutz;
- Sorgt für einen stabilen Getriebebetrieb bei niedrigen Temperaturen und trägt zum Kraftstoffverbrauch bei;
- Hat eine lange Lebensdauer.

Erfüllt Spezifikationen

SAE 80W-85 | API GL-4 |

Typische Kennwerte

Kinematic viscosity at 100 ˚C, mm²/c	12.0
Density at 20 ˚C, kg/m³	890
Viscosity index	95
Flash point in open crucible, ˚C	225
Temperature of hardening, ˚C	-25

Temperaturbereich

-20˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-013-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.