Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO TM-4 80W-90

Universelles Ganzjahres-Getriebeöl.

Beschreibung

Universelles Ganzjahres-Getriebeöl zur Schmierung von Stirnrad-, Kegel-, Kegelstirnrad- und Hypoidrädern, die b ei Berührungsspannungen b is 3000 MPa u nd Öltemperaturen b is 150 °C b etrieben werden.

Containertypen

Tin bucket 20L

Barrel 200L

In bulk

Vorteile

- unter verschiedenen Betriebsbedingungen über einen langen Zeitraum konstant hochwirksam;
- hat einen guten Schaum- und Korrosionsschutz, Kompatibilität mit Dichtungsmaterialien;
- hoher Verschleißschutz in einem weiten Temperaturbereich;
- reduziert den Verschleiß der Zahnräder und Lager erheblich;
- ein modernes Paket von Hochdruckadditiven bietet ein hohes Maß an Schutz für verschiedene Lasten, einschließlich Schlägen.

Erfüllt Spezifikationen

SAE 80W-90 | API GL4 |

Typische Kennwerte

Kinematic viscosity at 100 ˚C, mm²/c	15.0
Density at 20 ˚C, kg/m³	891
Viscosity index	95
Flash point in open crucible,˚C	225
Temperature of hardening,˚C	-23

Temperaturbereich

-20˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-013-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.