YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND SP

YUKO Tp-46 (ISO 68)

Öl für Seedampfturbine-Anlagen.

Beschreibung

Wird in Schiffsdampfturbinenanlagen (Getriebeturbineneinheiten) und anderen zusätzlichen hydraulisch angetriebenen Schiffsmechanismen eingesetzt.
Hergestellt aus hochwertigen Grundölen mit Additiven.

Containertypen

Barrel 200L

In bulk

Vorteile

- Hervorragende Oxidationsstabilität sorgt für eine lange Lebensdauer des Öls;
- Die hohen emulgierenden Eigenschaften ermöglichen die Verwendung des Öls auch unter Wasser;
- Verlängert die Lebensdauer der Geräte durch Verschleiß- und Reibungsschutzadditive.

Erfüllt Spezifikationen

ISO 68 |

Typische Kennwerte

Kinematic viscosity at 40˚C, mm²/s	68.0
Density at 20˚C, kg/m³	875
Viscosity index	94
Acid index, mg KOH/g	0.3
Flash point in open crucible, ˚C	230
Pour point, ˚C	-10

Temperaturbereich

-8˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-004:2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.