YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



IND

YUKO Transformer oil T-1500

Transformatoröl.

Beschreibung

Bestimmt zum befüllen von Leistungs- und Messwandlern, Ölbrüchen, Reaktoranlagen u nd anderen Hochspannungseinrichtungen als elektrische Hauptisolatoren, einschließlich der Funktion des Lichtbogenlöschmittels.
Hergestellt aus schwefelhaltigen Paraffingrundölen, unter Verwendung von lösungsmittelraffinierten u nd hydrierten Verfahren. Wird für u nter Spannung stehende Isolier- und Transformatoreinheiten, Wärmeabfuhr u nd Feuchtigkeitsschutz verwendet.

Containertypen

Barrel 200L

Vorteile

- Verbesserte Oxidationsstabilität;
- Fähigkeit des Öls, die Parameter im Dauerbetrieb aufrechtzuerhalten;
- Hohe Spannungsfestigkeit.

Erfüllt Spezifikationen

GOST 982-80 |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	7.9
Flash point in open crucible, ˚C	145
Acid index, mg KOH/g	0.005
Loss tangent of a dielectric at 90˚C, %	0.5
Pour point, ˚C	-45

Temperaturbereich

-43˚C 0 ˚C +50˚C

Produced according to GOST 982-80. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.