YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

YUKO PREMIUM

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO TSP-15K (GL-3)

Getriebeöl für KAMAZ-LKWs.

Beschreibung

Wird für Getriebe u nd Hauptgetriebe (zweistufige Getriebe mit Stirnrad- und Spiralkegelradgetrieben) von KAMAZ-Fahrzeugen u nd anderen Lkw eingesetzt.

Hergestellt aus mineralischen Grundölen mit Additiven.

Containertypen

Tin bucket 20L

Barrel 200L

In bulk

Vorteile

- Hat gute Tieftemperatureigenschaften;
- Schützt die Getriebeteile wirksam vor Verschleiß, Hochtemperaturablagerungen und Korrosion;
- Verhindert Schaumbildung.

Erfüllt Spezifikationen

SAE 85W-90 | API GL-3 |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	15.0
Density at 20˚C, kg/m³	905
Viscosity index	100
Flash point in open crucible, ˚C	200
Pour point, ˚C	-25

Temperaturbereich

-20˚C 0 ˚C +130˚C

Produced according to TU U 23.2-31852954-013-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product