YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL

YUKO TURBOSYNT DIESEL 10W-40

Halbsynthetisches Motoröl für Dieselmotoren.

Beschreibung

Bestimmt für moderne Luft- und Turbodieselmotoren von Pkw, Transportern u nd Lastkraftwagen u nd anderen Nutzfahrzeugen.

Hergestellt aus hochwertigen Fremdgrundölen mit Additiven, die während der gesamten Lebensdauer eine optimale Leistung b ieten.

Containertypen

Canister 1L | Canister 5L | Tin bucket 20L | Barrel 200L | In bulk

Vorteile

- Gleichbleibend hohe Leistung in verschiedenen Betriebsarten;
- Optimale Schmiereigenschaften und Reinigungskraft;
- Einfacher Kaltstart im Winter;
- Verhindert die Bildung von Ablagerungen bei hohen und niedrigen Temperaturen im Motor;
- Zuverlässiger Verschleißschutz der Motorteile über die gesamte Lebensdauer;
- Kompatibel mit allen Motordichtungen;

Erfüllt Spezifikationen

SAE 10W-40 | API CF-4/SG |

Typische Kennwerte

Kinematic viscosity at 100˚C, mm²/s	14.9
Density at 20˚C, kg/m³	885
Viscosity index	134
Alkalinity, mg KOH/g	8,5
Flash point in open crucible, ˚C	223
Pour point, ˚C	-32

Temperaturbereich

-27˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-045:2010. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.