Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



CVL IND SP

YUKO Uniol 2M2 (NLGI 0)

Spezielles, halbflüssiges Fett.

Beschreibung

Zur Schmierung von Mechanismen, die u nter hohen spezifischen Belastungen b etrieben werden: Reibungseinheiten von Industrieanlagen, Tunnelöfen, Heißförderbändern, Bergbau, Motor u nd Traktor, Landmaschinen, städtischer Elektrotransport, Keramikindustrie. Anwendungsbereich: Metallurgische Geräte.

Containertypen

Tin bucket 17,0kg

Barrel 170kg

Vorteile

- Hohe Antioxidations- und Schutzeigenschaften, insbesondere bei hohen Belastungen;
- Verfügbarkeit von Hochdruckzusätzen und Oxidationsinhibitoren;
- Lange Lebensdauer;
- Großer Temperaturbereich für den Einsatz.

Erfüllt Spezifikationen

NLGI 0 |

Typische Kennwerte

Effective viscosity at 0°C	100
Shear strength at 50°C	250
Dropping point, °C, min	250
Colloid stability, %	5.2
Volatility at 100°C per 1h	0.63
Penetration at 25°C with mixing, mm×10-1	360

Temperaturbereich

-30˚C 0 ˚C +160˚C

Produced according to TU U 20.5-31852954-058:2013. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.