YUKO.UA

Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com

YUKO PREMIUM



CVL IND

YUKO VMGZ (HV 15)

Hydrauliköl.

Beschreibung

Bestimmt für den ganzjährigen Einsatz in hydraulischen Steuerungen u nd Hydraulikgeräten von Bau-, Ernte-, Straßen-, Handhabungs- und anderen Geräten.

Hergestellt aus hochwertigen Grundölen mit Additiven.

Containertypen

Canister 20L

Barrel 200L

In bulk

Vorteile

- Hervorragende Viskositäts-Temperatur-Eigenschaften in einem weiten Temperaturbereich;
- Hohe Oxidations- und Chemikalienbeständigkeit;
- Kontinuierlicher Ölbetrieb im Hydrauliksystem;
- Schützt hydraulische Getriebekomponenten vor Verschleiß und Korrosion;
- Gute Antischaumeigenschaften.

Erfüllt Spezifikationen

ISO 15 | ISO HV |

Typische Kennwerte

Kinematic viscosity at 50˚C, mm²/s	14.7
Density at 20˚C, kg/m³	875
Viscosity index	130
Flash point in open crucible, ˚C	140
Pour point, ˚C	-50

Temperaturbereich

-47˚C 0 ˚C +45˚C

Produced according to TU U 23.2-31852954-003-2003. This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.