JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



YUKO ZhRO (NLGI 3)

Spezielles Eisenbahnfett.

Beschreibung

Wird zur Schmierung von Reibungseinheiten mit Wälzlagern der Lokomotiven, Dieselzüge, Triebzüge, Triebzüge, in Fahrmotorenlagern verwendet.
Bietet 400000 km Betriebszeit ohne Austausch u nd Wiederbefüllung für Elektrolokomotiven u nd Dieselaggregate.

Containertypen

Tin bucket 17,0kg

Barrel 170kg

Vorteile

- Hoher Wirkungsgrad bei niedrigen Temperaturen;
- Enthält Hochdruck- und Antioxidantien;
- Gute Antioxygen- und Schutzeigenschaften, insbesondere bei hohen Belastungen;
- Lange Entleerungszeit.

Erfüllt Spezifikationen

NLGI 3 |

Typische Kennwerte

Effective viscosity at 30°C	1750
Shear strength at 50°C	810
Dropping point, °C, min	202
Colloid stability, %	9,5
Volatibility at 100°C per 1h	1,2
Penetration at 25°C with mixing, mm×10-1	230

Temperaturbereich

-50˚C 0 ˚C +130˚C

Produced according to TU U 20.5-31852954-066:2014 This information is reference and it can be changed without a notice. This article is from 01/09/2014, it replaces all the early published descriptions of the product.