Produktdatenblat
Technical Data Sheet (TDS)

JV Yukoil LLC. Technical oils plant. 3A, Bazova str., Zaporozhzhia, Ukraine, 69014. +38 (061) 222 80 20, support@yukoil.com



SP

YUKO GT-79I

Spezielles Eisenbahnfett.

Beschreibung

Bestimmt für den Einsatz in Bremssystemen von Lokomotiven u nd Waggons zur Schmierung der Oberflächen „ Metall-Metall"; und „Metall-Kautschuk" ;. Die Schmierung ist b ei Temperaturen von minus 60°C b is 120°C (kurzzeitig b is 150°C) wirksam.

Containertypen

- Tin 800g
- Tin bucket 17,0kg

Vorteile

- Hochtemperatur-Performance bei niedrigen Temperaturen;
- Verursacht kein Anschwellen der Gummidichtungen von automatischen Bremsmechanismen;
- Enthält einen antioxidativen Zusatz;
- Kann in anderen Branchen, im Verkehr und in der Landwirtschaft eingesetzt werden.

Erfüllt Spezifikationen

NLGI 2 |

Typische Kennwerte

Appearance	homogeneous light-brown or light-yellow ointment
Effective viscosity at minus 55°C, max	1600
Shear strength at 50°C	250
Dropping point, °C, min	180
Colloidal stability, %, not more	15
Evaporation, %, max	2,5
Penetration at 25°C with mixing, mm×10-1	240-290

Temperaturbereich

-60˚C 0 ˚C +120˚C

Produced according to TU U 20.5-31852954-066:2014. This information is reference and it can be changed without a notice.